



BRASS VALVES Ball | Gate | Check

The C&C branded brass valves consists of multiple configurations of ball valves, check valves, and gate valves. These products are ideal for a variety of media and are highly resistant to corrosion. Available sizes between 3/8" - 4" and pressures ranging from 200 psi to 600 psi.

Check Valve - Threaded



- **Sizes:** 3/8" 4"
- Pressure: 200 PSI NSCWP
- **Design:** Metal seated

Ball Valve - Threaded



- Sizes: 1/4" 4" (full port)
- Pressure: 600 PSI NSCWP
- **Design:** Chrome plated ball, PTFE seat, locking handle

Check Valve - Threaded

- 2 300CWP CXC
 - Sizes: 1" 4"
 - Pressure: 300 PSI NSCWP
 - Design: O-Ring style
 - 90 Durometer

Heavy Duty Ball Valve - Threaded

- Sizes: 1" 4" (full port)
- Pressure: 600 PSI NSCWP
- **Design:** Chrome plated ball, PTFE seat, locking handle

Check Valve - Grooved



- **Sizes:** 2" 4"
- Pressure: 300 PSI NSCWP
- Design: O-Ring style
 - 90 Durometer

Quick Open & Standard Gate Valves



- Sizes: 1/4" 4"
- Pressure: 200 PSI NSCWP
- Seal: PTFE

10350 Clay Road • Suite 250 • Houston, TX • 77041 • Toll Free: (844) 398-6449 • www.cncflowcontrol.com